



NATURHAUS Antifungal Primer Oil

Product information: NATURHAUS *Antifungal Primer Oil* is a deeply penetrating wood primer/sealer for interior and specifically exterior use. The product creates an elastic, breathable, wood- and wood-grain enhancing surface. Use as a primer and/or sealer for all absorbent surfaces made of wood. It can also be applied to fix protective salts. The product is specifically recommended for the priming and maintenance of exterior wooden floors.

NATURHAUS Antifungal Primer Oil contains synthetic antifungal substances which are not toxic to warm-blooded organisms.

Ingredients: Linseed oil, wood oil standoil, natural rosin esters, antifungal additive (chlorine-free isothiazolone derivative) triple-refined orange oil, lead-free driers (Co, Zr fatty acid salts) with < 0.1 % fatty acid cobaltate.

Application: NATURHAUS *Antifungal Primer Oil* is applied undiluted by brushing, spraying, rolling or dipping. Two to three coats of this product are recommended. Highly absorbent surfaces and specifically cross-cut wood surfaces will perform best with three coats. Sand the untreated wood with 120-grit to 150-grit sandpaper. Between successive coats, a light buffing with 150-grit to 180-grit sandpaper will result in a smoother finish. Cross-cut wood may additionally be protected by NATURHAUS *Pore Filler* (Prod. No. 00450). The maximum moisture content for exterior areas should not exceed 15 percent (interior areas 12 percent). Clean spots and tools with NATURHAUS *Resin & Oil Thinner* (Prod. No. 00500).

Further treatment: NATURHAUS *Resin & Oil Finish, translucent & covering* (Prod. No. 03000 to 03600).

Drying time: approximately 6 - 8 hours, depending on temperature and relative humidity. Do not use at temperatures below +10 °C.

Physical properties: Density: approx. 0.89 g/ml; viscosity approx. 13 seconds (ISO 2431, 4 mm).

Coverage: 8 - 12 m² per l (80 - 120 g/m²), depending on absorbency of the surface.

Test specifications: DIN EN 71-3 (security requirements for toys intended for children).

Hazard classification: **Flammable liquid (R10)** according to *Council Directive 1999/45/EEC*.

Storing conditions: Keep the original container tightly closed and store in a dry, cool, frost-free and well ventilated area. The product can be stored up to 2 years.

Security and disposal information: Keep product away from children. Do not use in spray cabins where nitrocellulose laquers are processed. Keep away from sources of ignition and refrain from smoking. Ventilate working area during application and drying. Crumpled, soaked cloths may self-ignite at insufficient air supply. Therefore, spread out soaked cloths after use and allow to air-dry or store in a plastic container filled with water before disposal with the domestic waste to avoid the **Danger of self-ignition!** Do not allow to enter drains, surface waters and groundwater. Empty containers completely and send to a licensed recycler. Dispose of used or contaminated product in accordance with local authority requirements. For further information, please ask for our EC material safety data sheet.

Product No: 00208

Pack size,	750 ml	2.5 l	5 l	10 l	25 l	200 l
Container material:	tinplate	tinplate	tinplate	tinplate	tinplate	metal drum