



## NATURHAUS-Fantastic

- Product information:** NATURHAUS Fantastic is quick-drying all-weather oil providing deep penetration, protection against blue stain and a wear layer. The colorless surface protection provides a slight silky glaze, strong water repellent action and is suitable for wood outdoors (Durability classes 1-3, e.g., teak, merbau, bankirai, oak, larch, meranti as per EN 350- 1-2; DIN 68800; and the old classification as per DIN 68364). It is not suitable for windows, doors and gates by itself. The product provides a vapor-permeable, open-pored treatment that highlights and accentuates the wood grain slightly. The product is suitable for the fixation of protective salts. NATURHAUS Fantastic can also be used indoors primarily in damp locations. Fantastic can be shaded with all colored NATURHAUS oil products.
- Ingredients:** Refined linseed oil, linseed stand oil, tung stand oil, natural resin ester, freshly distilled limonene, lead-free siccatives (Ca/Co/Zr fatty acids with < 0.1% cobalt fatty acid), blue stain inhibitor (chlorine-free isothiazolinone derivative with synthetic active ingredients to prevent infestation by blue stain and that present no hazard to warm-blooded animals).
- Use:** NATURHAUS *Fantastic* is ready to use and is applied by spraying, painting or rolling. For a dipping application, see the physical data. Before use, sand using 150-grit. To obtain good protection against moisture, a second coat is necessary. Comply with the drying times before each coat. After the first coat, sand using 180-grit to 240-grit paper and smooth textured surfaces using a medium-fine pad. The moisture content of the wood must not exceed 15%. Clean equipment using NATURHAUS *Resin and Oil Thinner* (Item No. 00500).
- Post-treatment:** NATURHAUS *Fantastic*, NATURHAUS *Resin and Oil*, colored, transparent and covering  
Two coats of a pigmented Resin and Oil finish must be applied to wood windows, doors and gates.
- Cleaning and care:** Clean using NATURHAUS *Wood Restorer* (Item No. 09200). This applies to both pressure-treated wood surfaces and weathered surfaces that must then be treated again. Surfaces cleaned and treated with NATURHAUS *Fantastic* can be maintained using NATURHAUS *Fantastic* without being sanded in advance. In addition, NATURHAUS *Fantastic* is a care product intended for all oiled woods used outdoors.
- Drying time:** Approx. 6-8 hours or overnight (20°C, 65% relative humidity)  
**Do not use the product at temperatures below +10°C or in direct sunlight!**
- Physical data:** Density: approx. 0.900 g/ml; viscosity: approx. 16 seconds (DIN 53211, 4 mm cup). Adjust the dipping viscosity to 12-13 seconds using thinner, Item No. 00500.
- Coverage:** First coat: 12-9 m<sup>2</sup>/l (corresponding to 70-100 g/m<sup>2</sup>), depending on the type of wood and type of application  
Second coat: 45-22 m<sup>2</sup>/l (corresponding to 20-40 g/m<sup>2</sup>) and for each additional coat
- Shelf life:** The product can be stored for at least two years if kept cool, dry and above freezing in the sealed original container.
- Markings:** Hazardous to the environment, irritant, flammable, sensitivity possible through skin contact, toxic to aquatic organisms, may have damaging effects in waters over the long term.
- Safety and disposal notes:** Allow materials soaked in the product such as rags, sponges, paper, sanding dust and clothing to dry spread out in a well-ventilated location or store for several days in a plastic container filled with water because of the **danger of spontaneous combustion** if dried without adequate ventilation. Cloths with completely cured residue may be disposed of with domestic trash or incinerated. Avoid skin contact. Wear suitable protective gloves. Keep away from ignition sources -- do not smoke. During use and while drying, ventilate inside areas well. Do not use in spraying equipment or in front of suction equipment that is used for conventional paint. Recycle completely empty containers. Keep away from children. If swallowed, contact a doctor immediately, providing the packaging or label. Obey the directions in the EC Material Safety Data Sheet.
- Item No.:** 00203
- |  |                     |                    |                  |                   |                   |                     |
|--|---------------------|--------------------|------------------|-------------------|-------------------|---------------------|
| <b>Container sizes, container material</b> | 750 ml<br>Tin plate | 2.5 l<br>Tin plate | 5 l<br>Tin plate | 10 l<br>Tin plate | 25 l<br>Tin plate | 200 l<br>Metal drum |
|--|---------------------|--------------------|------------------|-------------------|-------------------|---------------------|

