



NATURHAUS Hard Oil High Solid

Product information:	NATURHAUS <i>Hard Oil High Solid</i> is a high-solids interior and exterior primer oil that excels at sealing medium-to-high traffic wood flooring, dry and absorbent woods, and large surfaces such as floors and architectural woodwork. It is also our recommendation for finishing garden furniture. NATURHAUS <i>Hard Oil High Solid</i> is a deeply penetrating wood primer/sealer that creates an elastic, breathable, wood-and wood-grain enhancing surface.				
Ingredients:	Linseed standoil, wood oil standoil, natural rosin esters, < 5 % of triple-refined orange oil, lead-free driers (Co, Zr fatty acid salts) with < 0.1 % fatty acid cobaltate.				
Application:	NATURHAUS <i>Hard Oil High Solid</i> is applied undiluted by hot spraying (60 °C) or industrial rolling. For manual application use a paint scraper or a lint-free cloth for furniture. Spread sufficient oil to saturate absorbent areas. After a residence time of 30-60 minutes grind in the wet oil using a suitable single disk floor machine (green or brown pad), an eccentric grinder with a medium rough pad or a suitable brush, e.g. 220-grit Edruflex, or in case of furniture, with an eccentric grinder with a medium rough pad or a lint-free cloth. After a drying time of approximately 24 hours the surface may be treated with an additional coat. Apply only thin layers on pre-treated surfaces. The humidity of the wood should not exceed 12 %. Clean spots and tools with NATURHAUS <i>Resin & Oil Thinner (Prod. No. 00500)</i> .				
Pretreatment:	A pretreatment of desk tops, high traffic areas and garden furniture with NATURHAUS <i>Hard oil "High Performance" (Prod. No. 00250)</i> is recommended.				
Further treatment:	NATURHAUS <i>Hard Wax (Prod. No. 01050)</i>				
Drying time:	approximately 12 hours, depending on climate, temperature, humidity and absorbency.				
Physical properties:	Density: approx. 0.89 g/ml; viscosity approx. 19 seconds (ISO 2431, 4 mm).				
Coverage:	50 - 80 m ² per l (10 - 20 g/m ²), depending on absorbency of surface.				
Test specifications:	DIN EN 71-3 (security requirements for toys intended for children).				
Hazard classification:	The product does not require labelling according to <i>Council Directive 1999/45/EEC</i> .				
Storing conditions:	Keep the original container tightly closed and store in a dry, cool, frost-free and well ventilated area. The product can be stored up to 2 years.				
Security and disposal information:	Keep product away from children. Do not use in spray cabins where nitrocellulose laquers are processed. Keep away from sources of ignition and refrain from smoking. Ventilate working area during application and drying. Crumpled, soaked cloths may self-ignite at insufficient air supply. Therefore, spread out soaked cloths after use and allow to air-dry or store in a plastic container filled with water before disposal with the domestic waste to avoid the Danger of self-ignition! . Do not allow to enter drains, surface waters and groundwater. Empty containers completely and send to a licensed recycler. Dispose of used or contaminated product in accordance with local authority requirements. For further information, please ask for our EC material safety data sheet.				
Product No:	00214				
Pack size, Container material:	750 ml tinplate	2.5 l tinplate	10 l tinplate	25 l tinplate	200 l metal drum

The information herein is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it is intended. No warranty, express or implied, is made. In case of ambiguities between the German and the English version, the actual German version will be valid. (Version 004 / January 2005)