



NATURHAUS Hardwax Oil

Product information:	NATURHAUS <i>Hardwax Oil</i> is a deep, wood-enhancing penetrating interior oil finish for medium-to-high traffic areas. The product creates a breathable, moisture-regulating, dirt-resistant, waxy finish with superior water-resistant qualities. Depending on the application technique a semi gloss or satin sheen surface may be obtained. The product enhances the wood and the wood-grain only slightly and is therefore specifically useful in the treatment of light-coloured softwood (e.g. beech, birch, maple).					
Ingredients:	Linseed standoil, wood oil standoil, natural rosin esters, unbleached carnauba wax, bentonite triple-refined orange oil, lead-free driers (Co, Zr fatty acid salts) with < 0.1 % fatty acid cobaltate.					
Application:	<u>Semi gloss surfaces:</u> NATURHAUS <i>Hardwax Oil</i> is applied undiluted and at least twice by brushing, spraying, rolling or scraping. Allow to dry before spreading a new layer. <u>Satin sheen surfaces:</u> NATURHAUS <i>Hardwax Oil</i> is applied at least twice by brushing, spraying, rolling or scraping. Grind the product in using a suitable single disk floor machine (green pad), or an eccentric grinder with a medium rough pad. The humidity of the wood should not exceed 12 %. Clean spots and tools with NATURHAUS <i>Resin & Oil Thinner (Prod. No. 00500)</i> .					
Drying time:	approximately 8 hours, depending on climate, temperature and humidity.					
Resistance:	The NATURHAUS <i>Hardwax Oil</i> reaches the optimal resistance after a curing period of about 14 days. Until then the surface has to be only dry-cleaned and not permanently covered with e.g. carpets or blankets.					
Physical properties:	Density: approx. 0.89 g/ml; viscosity approx. 18 seconds (ISO 2431, 4 mm).					
Coverage:	15 - 25 m ² per l (40 - 70 g/m ²), for a satin-finished surface 30 - 50 m ² per l (20 - 30 g/m ²), for a semi gloss surface.					
Test specifications:	DIN EN 71-3 (security requirements for toys intended for children).					
Hazard classification:	Flammable liquid (R10) according to <i>Council Directive 1999/45/EEC</i> .					
Storing conditions:	Keep the original container tightly closed and store in a dry, cool, frost-free and well ventilated area. The product can be stored up to 2 years.					
Security and disposal information:	Keep product away from children. Do not use in spray cabins where nitrocellulose laquers are processed. Keep away from sources of ignition and refrain from smoking. Ventilate working area during application and drying. Crumpled, soaked cloths may self-ignite at insufficient air supply. Therefore, spread out soaked cloths after use and allow to air-dry or store in a plastic container filled with water before disposal with the domestic waste to avoid the Danger of self-ignition! Do not allow to enter drains, surface waters and groundwater. Empty containers completely and send to a licensed recycler. Dispose of used or contaminated product in accordance with local authority requirements. For further information, please ask for our EC material safety data sheet.					
Product No:	01500					
Pack size,	750 ml	2.5 l	5 l	10 l	25 l	200 l
Container material:	interior coated tinplate	interior coated tinplate	interior coated tinplate	interior coated tinplate	interior coated tinplate	metal drum

The information herein is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it is intended. No warranty, express or implied, is made. In case of ambiguities between the German and the English version, the actual German version will be valid. (Version 003 / Dezember 2004)