



NATURHAUS Hardwax "White"

Product information:	NATURHAUS <i>Hardwax "White"</i> is a solvent-free wax finish for interior wooden surfaces such as floors, stairways, doors, wooden furniture and other surfaces that have previously been treated with our oils. The product creates an elastic, breathable, wood-and wood-grain enhancing, dirt and dust resistant anti-static seal with a satin sheen.				
Ingredients:	Linseed oil, unbleached beeswax and carnauba wax, titanium dioxide (pigment white), lead-free driers (Co, Zr fatty acid salts) with < 0.1 % fatty acid cobaltate.				
Pretreatment	Depending on the desired durability of the surface to be waxed, a pretreatment with NATURHAUS <i>Shellac Primer (Prod. No. 00220-00230)</i> , NATURHAUS <i>Natural Resin Primer "High filling" (Prod. No. 92809)</i> , NATURHAUS <i>Hard Oil (Prod. No. 00210)</i> , NATURHAUS <i>Hard Oil "High Solid" (Prod. No. 00214)</i> , NATURHAUS <i>Hard Oil High Performance "White" (Prod. No. 00251)</i> or Naturhaus <i>Hard Wax Oil "White" (Prod. No. 01501)</i> is recommended.				
Application:	<p>The surface to be waxed must be dry, non-absorbent, clean, and free of contaminants such as grease. On surfaces finished with our oils, the oil must be completely cured before applying this wax. This product requires several days to cure. Freshly waxed surfaces should be kept free of moisture and heavy foot traffic for about a week or so. NATURHAUS <i>Hardwax "White"</i> should be applied in a thin, even coat with a lint-free cloth. The surface should then be thoroughly buffed with a dry cloth or brush after two to four hours. For an even harder finish, the wax can be rebuffed two to four days after the initial buffing.</p> <p>For professional use hot wax machine application such as mk "Duoline" or mk-"Airtherm" hot wax spraying system with manual or automatic spray guns is recommended. Industrial rolling has also proven to be effective. Machine buff within 60 minutes after application using a suitable single disk floor machine with a green pad, an eccentric grinder with a medium rough pad or a suitable brush. Rebuff after a minimum curing time of two hours after the initial buffing using a dry, lint-free cloth, a horsehair bristle or a white buffing pad.</p> <p>Clean spots and tools with NATURHAUS <i>Resin & Oil Remover (Prod. No. 09100)</i> or <i>Resin & Oil Thinner (Prod. No. 00500)</i>.</p>				
Drying time:	approximately 12 hours, depending on climate, temperature and humidity. The wax coating reaches optimal resistance after a curing time of about 14 days. Until then the surface should only be dry-cleaned and not permanently covered with e.g. carpets or blankets.				
Physical properties:	Density: approx. 0.90 g/ml; pasty.				
Coverage:	60 - 450 m ² per l (2 - 15 g/m ²), depending on application technique and surface.				
Test specifications:	DIN EN 71-3 (security requirements for toys intended for children).				
Hazard classification:	The product does not require labelling according to <i>Council Directive 1999/45/EEC</i> .				
Storing conditions:	Keep the original container tightly closed and store in a dry, cool, frost-free and well ventilated area. The product can be stored up to 2 years.				
Security and disposal information:	Keep product away from children. Do not use in spray cabins where synthetic laquers are processed. Refrain from smoking. Ventilate working area during drying. Crumpled, soaked cloths may self-ignite at insufficient air supply. Therefore, spread out soaked cloths after use and allow to air-dry or store in a plastic container filled with water before disposal with the domestic waste to avoid the Danger of self-ignition! . Do not allow to enter drains, surface waters and groundwater. Empty containers completely and send to a licensed recycler. Dispose of used or contaminated product in accordance with local authority requirements. For further information, please ask for our EC material safety data sheet.				
Product No:	01051				
Pack size,	35 ml	250 ml	500 ml	2.5 l	10 l
Container material:	tinplate	tinplate	tinplate	tinplate	tinplate

The information herein is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it is intended. No warranty, express or implied, is made. In case of ambiguities between the German and the English version, the actual German version will be valid. (Version 004 / January 2005)