



NATURHAUS Natural Resin Primer “Clear”

Product information: NATURHAUS *Natural Resin Primer “Clear”* is an alcohol-based, fast-drying, slightly film-forming interior primer, sealer and/or undercoat. It contains natural resins such as shellac and copal, and has been specifically developed for brightening NATURHAUS *Natural Resin Patina Stains* (Prod. Nos. 92901 - 92910) and *Natural Resin Primers “Coloured”* (Prod. Nos. 92850 - 92861). Its use as a sealer prior to the application of coloured NATURHAUS products will result in a more even colour distribution.

Ingredients: Unbleached shellac, copal, natural rosin ester, ethanol and triple-refined orange oil.

Application: **① Brightening of Coloured NATURHAUS Natural Resin Products:**
Add product in any ratio to NATURHAUS *Natural Resin Patina Stains* (Prod. Nos. 92901 - 92910) and NATURHAUS *Natural Resin Primers “Coloured”* (Prod. Nos. 92850 - 92861) and mix thoroughly to the desired end tone.

② Sealing of Wooden Surfaces before Colouring:

Grind surface with 180-grit to 240-grit sandpaper and apply product using airmix spraying techniques.. Allow to dry for 20 to 60 minutes. The maximum moisture content for softwoods and hardwoods should not exceed 12 percent.

Clean spots and tools with NATURHAUS *Alcohol Thinner* (Prod. No. 92801).

Further treatment: NATURHAUS *Hard Oils* (Prod. Nos. 00210, 00214, 00250), NATURHAUS *Hard Wax* (Prod. No. 01050), NATURHAUS *Hard Wax Oil* (Prod. No. 01500).

Drying time: approximately 20 - 60 minutes, depending on temperature and relative humidity.

Physical properties: Density: approx. 0.82 g/ml; viscosity approx. 11 seconds (ISO 2431, 4 mm).

Coverage: 17 - 85 m² per l (10 - 50 g/m²), depending on the absorbency of the surface.

Test specifications: DIN EN 71-3 (security requirements for toys intended for children).

Hazard classification: *Highly flammable (F, R11)* according to *Council Directive 1999/45/EEC*.

Storing conditions: Keep the original container tightly closed and store in a dry, cool, frost-free and well ventilated area. The product can be stored up to 2 years.

Security and disposal information: Keep product away from children. Keep away from sources of ignition and refrain from smoking. Ventilate working area during application and drying. Do not allow to enter drains, surface waters and groundwater. Empty containers completely and send to a licensed recycler. Dispose of used or contaminated product in accordance with local authority requirements. For further information, please ask for our EC material safety data sheet.

Product No: 92900

Pack size,	750 ml	2.5 l	10 l
Container material:	tinplate	tinplate	tinplate

