



NATURHAUS Resin & Oil Finish, translucent & covering

Product information:	<p>NATURHAUS <i>Resin & Oil Finish, translucent & covering</i> is one of our most versatile products. It's a stain and finish in one, has exceptional coverage, and will reveal and enhance the natural attributes of all surfaces made of wood, stone, and clay. It is available in many different colours miscible in all proportions and will colorize and preserve interior and exterior architectural woodwork such as doors and windows, moldings and trim, stairways and balustrades, furniture, cabinetry, and mantelpieces. It is appropriate for large details such as porches, floors, wood siding, greenhouses, and log homes. It can also be safely used for children's furniture such as baby cribs, high chairs, tables and toys. You may also want to consider it for rejuvenating exterior woods that have been bleached and grayed by the sun. It will provide UV protection (with the exception of #03000 "Clear"), and build an elastic, water-resistant finish that will weather well. It can be used to help preserve garden accessories, and will also perform well on masonry such as stone tiles, clay pots, and the like. Use it on your decorative objects and for antiquing furniture. It dries to a glossy sheen.</p> <p>For exterior surfaces a dry film thickness of not less than 80 µm is required for optimal weather resistance.</p>			
Ingredients:	<p>Linseed standoil, wood oil standoil, natural rosin esters, triple-refined orange oil, lead-free driers (Co, Zr fatty acid salts) with < 0.1 % fatty acid cobaltate. The coloured resin & oil finishes further contain varying amounts of natural and synthetic pigments, and bentonite.</p>			
Application:	<p>NATURHAUS <i>Resin & Oil Finish, translucent & covering</i> is applied undiluted after stirring in a figure eight motion at least twice by brushing or rolling. For spray application, please dilute with appropriate amounts of NATURHAUS <i>Resin & Oil Thinner (Prod. No. 00500)</i> and filtrate through a fine sieve prior to use. Surfaces should be sound, dust-free, and free of contaminants such as oil and grease. The moisture content of the wood should not exceed 15 percent. Allow to dry between successive coats. Clean spots and tools with NATURHAUS <i>Resin & Oil Thinner (Prod. No. 00500)</i>.</p>			
Pre-treatment:	<p>NATURHAUS <i>Primer Oil (Prod. No. 00200)</i>, NATURHAUS <i>Antifungal Primer Oil (Prod. No. 00208)</i>, NATURHAUS <i>Pore Filler (Prod. No. 00450)</i></p>			
Drying time:	<p>approximately 6 - 12 hours, depending on climate, temperature and humidity. Do not use at temperatures below +10 °C and at full summer sunshine.</p>			
Physical properties:	<p>Density: approx. 0.90 - 0.97 g/ml; viscosity approx. 17 - 25 seconds (ISO 2431, 4 mm).</p>			
Coverage:	<p>10 - 16 m² per l (60 - 90 g/m²), depending on the absorbency of the surface.</p>			
Test specifications:	<p>DIN EN 71-3 (security requirements for toys intended for children).</p>			
Hazard classification:	<p>Flammable liquid (R10) according to <i>Council Directive 1999/45/EEC</i>.</p>			
Storing conditions:	<p>Keep the original container tightly closed and store in a dry, cool, frost-free and well ventilated area. The product can be stored up to 2 years.</p>			
Security and disposal information:	<p>Keep product away from children. Do not use in spray cabins where nitrocellulose laquers are processed. Keep away from sources of ignition and refrain from smoking. Ventilate working area during application and drying. Crumpled, soaked cloths may self-ignite at insufficient air supply. Therefore, spread out soaked cloths after use and allow to air-dry or store in a plastic container filled with water before disposal with the domestic waste to avoid the Danger of self-ignition! Do not allow to enter drains, surface waters and groundwater. Empty containers completely and send to a licensed recycler. Dispose of used or contaminated product in accordance with local authority requirements. For further information, please ask for our EC material safety data sheet.</p>			
Product Nos:	<p>03000 to 03600 (for available tones, please refer to our order lists)</p>			
Pack size, Container material:	750 ml tinplate	2.5 l tinplate	10 l tinplate	25 l tinplate

The information herein is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it is intended. No warranty, express or implied, is made. In case of ambiguities between the German and the English version, the actual German version will be valid. (Version 003 / Dezember 2004)